


4.8.1.2.2 Entrata da 8 a 50 mm



										Nº
8	621 – 900	680	125 / 120	236 – 375	N	N	1	Roto Sil	242726	
	901 – 1200	980	200 / 200	298 – 448	J	N	1	Roto Sil	791986	
15	431 – 620	500	100 / 100	225 – 350	N	N	–	Roto Sil	233418	
25	621 – 800	630	100 / 100	393 – 482	J	N	1	Roto Sil	763125	
30	801 – 1200	980	200 / 200	482 – 682	J	N	1	Roto Sil	763126	
35										
40										
45										
50										
8	1201 – 1600	1380	200 / 200	448 – 658	J	N	2	Roto Sil	763127	
15	1601 – 2000	1780	200 / 200	680 – 880	J	J	2	Roto Sil	795482	
25	2001 – 2400	2180	200 / 200	880 – 1080	J	J	4	Roto Sil	795484	
30										
35										
40										
45										
50										



INFORMAZIONI

Per l'asta leva di finestre a due ante RC 2 / RC 2 N è necessario un gancio d'arresto. Vedere → *da pagina 662*.



INFORMAZIONI

Dispositivo falsa manovra (arresto asta leva) premontato di serie.



INFORMAZIONI

Nell'utilizzo di aste leva standard (RC 1 N, RC 2, RC 2 N) utilizzare la guida articolazione per anta a ventola → *da pagina 525*