


#### 4.8.2.2 Entrata da 8 a 50 mm



|    |             |      |           |            |   |   | # |          | Nº      |
|----|-------------|------|-----------|------------|---|---|---|----------|---------|
| 8  | 431 – 620   | 400  | 100 / 100 | 194 – 289  | N | N | – | Roto Sil | 2007128 |
| 15 | 621 – 800   | 680  | 100 / 100 | 290 – 379  | J | N | 1 | Roto Sil | 2007129 |
| 25 | 801 – 1200  | 980  | 200 / 200 | 380 – 579  | J | N | 1 | Roto Sil | 2007130 |
| 30 |             |      |           |            |   |   |   |          |         |
| 35 | 1001 – 1400 | 1180 | 200 / 200 | 480 – 679  | J | N | 1 | Roto Sil | 2007131 |
| 40 | 1201 – 1600 | 1380 | 200 / 200 | 580 – 779  | J | N | 2 | Roto Sil | 2007132 |
| 45 | 1601 – 2000 | 1780 | 200 / 200 | 780 – 979  | J | J | 2 | Roto Sil | 2007133 |
| 50 | 2001 – 2400 | 2180 | 200 / 200 | 980 – 1179 | J | J | 4 | Roto Sil | 2007134 |



#### INFORMAZIONI

Dispositivo falsa manovra (arresto asta leva) premontato di serie.



#### INFORMAZIONI

Qualora si utilizzi l'asta leva Plus (RC 1 N, RC 2, RC 2 N), utilizzare la guida articolazione sicurezza base (anta ribalta), oppure la guida articolazione di sicurezza (anta ribalta) → *da pagina 524*

#### 4.8.3 Cava euro 7/8

##### 4.8.3.1 Sede maniglia costante



|    |             |      |     |     |   |   | # |          | Nº     |
|----|-------------|------|-----|-----|---|---|---|----------|--------|
| 15 | 431 – 630   | 520  | 200 | 195 | J | N | – | Roto Sil | 839919 |
| 25 | 601 – 800   | 690  | 200 | 335 | J | N | – | Roto Sil | 331943 |
| 30 | 801 – 1000  | 890  | 200 | 490 | J | N | – | Roto Sil | 331964 |
| 35 |             |      |     |     |   |   |   |          |        |
| 40 |             |      |     |     |   |   |   |          |        |
| 45 |             |      |     |     |   |   |   |          |        |
| 50 |             |      |     |     |   |   |   |          |        |
| 8  | 1001 – 1200 | 1090 | 200 | 335 | J | N | 1 | Roto Sil | 331965 |
| 15 | 1201 – 1400 | 1290 | 200 | 335 | J | N | 1 | Roto Sil | 331966 |
| 25 | 1401 – 1600 | 1490 | 200 | 335 | J | N | 1 | Roto Sil | 331967 |
| 30 | 1601 – 1800 | 1690 | 200 | 335 | J | J | 2 | Roto Sil | 331968 |
| 35 | 1801 – 2000 | 1890 | 200 | 640 | J | J | 2 | Roto Sil | 331969 |
| 40 | 2001 – 2200 | 2090 | 200 | 640 | J | J | 2 | Roto Sil | 331970 |
| 45 | 2201 – 2400 | 2290 | 200 | 640 | J | J | 2 | Roto Sil | 331971 |
| 50 |             |      |     |     |   |   |   |          |        |



#### INFORMAZIONI

Per ogni asta leva è necessario un terminale per cava Euro 7/8. Vedere → *da pagina 486*.