



INFORMAZIONI

A partire da ABB 2401 mm, è necessaria una chiusura centrale.

4.8.2.1.2 Entrata da 8 a 50 mm



8	431 – 710	600	200	144	J	N	–	J	– / 1	– / P	Roto Sil	2007106
15	601 – 800	690	200	234	J	N	–	–	–	–	Roto Sil	2007116
25	801 – 1000	890	200	396	J	N	1	–	–	–	Roto Sil	2007117
30	1001 – 1200	1090	200	496	J	N	1	–	–	–	Roto Sil	2007118
35	1201 – 1400	1290	200	546	J	N	1	–	–	–	Roto Sil	2007119
40	1401 – 1600	1490	200	546	J	N	2	–	–	–	Roto Sil	2007120
45	1601 – 1800	1690	200	546	J	J	2	–	–	–	Roto Sil	2007121
50	1801 – 2000	1890	200	546	J	J	2	–	–	–	Roto Sil	2007122
	2001 – 2200	2090	200	546	J	J	3	–	–	–	Roto Sil	2007123
	2201 – 2400	2290	200	546	J	J	3	–	–	–	Roto Sil	2007124



INFORMAZIONI

Dispositivo falsa manovra (arresto asta leva) premontato di serie.



INFORMAZIONI

Qualora si utilizzi l'asta leva Plus (RC 1 N, RC 2, RC 2 N), utilizzare la guida articolazione sicurezza base (anta ribalta), oppure la guida articolazione di sicurezza (anta ribalta) → *da pagina 524*