


4.3.2.2 Sede maniglia centrale/variabile




15	310 – 620	430	100 / 100	155 - 225	N	N	N	–	–	Roto Sil	259717
	310 – 850	630	200 / 200	155 - 425	N	N	N	–	–	Roto Sil	742202
	621 – 800	580	90 / 90	311 - 400	N	J	N	–	–	Roto Sil	289862
			90 / 90	311 - 400	N	J	N	1	E	Roto Sil	259719
	801 – 1200	980	200 / 200	401 - 600	N	J	N	–	–	Roto Sil	289863
			200 / 200	401 - 600	N	J	N	1	E	Roto Sil	259720
			200 / 200	401 - 600	J	J	N	1	E	Roto Sil	318596
	1001 – 1400	1180	200 / 200	501 - 700	J	J	N	2	E	Roto Sil	796459
	1201 – 1600	1380	200 / 200	601 - 800	N	J	N	–	–	Roto Sil	289864
			200 / 200	601 - 800	N	J	N	2	E	Roto Sil	259721
			200 / 200	601 - 800	J	J	N	2	E	Roto Sil	318597
	1601 – 2000	1780	200 / 200	801 - 1000	N	J	J	–	–	Roto Sil	289865
			200 / 200	801 - 1000	J	J	J	2	E	Roto Sil	795389
	2001 – 2400	2180	200 / 200	1001 - 1200	N	J	J	–	–	Roto Sil	289866
			200 / 200	1001 - 1200	J	J	J	4	E	Roto Sil	795392



INFORMAZIONI

A partire da ABB 2401 mm, è necessaria una chiusura centrale.

4.3.2.3 Sede maniglia centrale/variabile - Sicurezza



15	310 – 620	430	100 / 100	155 - 225	N	N	N	–	–	Roto Sil	259717
	621 – 800	580	90 / 90	311 - 400	N	J	N	1	V	Roto Sil	355743
	801 – 1200	980	200 / 200	401 - 600	N	J	N	1	V	Roto Sil	355744
	1201 – 1600	1380	200 / 200	601 - 800	N	J	N	2	V	Roto Sil	355745
	1601 – 2000	1780	200 / 200	801 - 1000	J	J	J	2	V	Roto Sil	795390
	2001 – 2400	2180	200 / 200	1001 - 1200	J	J	J	4	V	Roto Sil	795393