


4.8.1.2.2 Entrata da 8 a 50 mm



8	431 – 710	600	200	233	N	N	N	–	Roto Sil	795442 <input type="checkbox"/>
	601 – 800	690	200	195	N	N	1	Roto Sil	242731 <input type="checkbox"/>	
	801 – 1000	890	200	195	J	N	1	Roto Sil	791977 <input type="checkbox"/>	
15 25 30 35 40 45 50	431 – 710	600	200	195	J	N	–	Roto Sil	795464 <input type="checkbox"/>	
	601 – 800	690	200	335	J	N	1	Roto Sil	791975 <input type="checkbox"/>	
	801 – 1000	890	200	490	J	N	2	Roto Sil	791976 <input type="checkbox"/>	
8 15 25 30 35 40 45 50	1001 – 1200	1090	200	335	J	N	2	Roto Sil	791978 <input type="checkbox"/>	
	1201 – 1400	1290	200	335	J	N	2	Roto Sil	791979 <input type="checkbox"/>	
	1401 – 1600	1490	200	335	J	N	3	Roto Sil	791980 <input type="checkbox"/>	
	1601 – 1800	1690	200	335	J	J	3	Roto Sil	795466 <input type="checkbox"/>	
	1801 – 2000	1890	200	640	J	J	3	Roto Sil	795469 <input type="checkbox"/>	
	2001 – 2200	2090	200	640	J	J	4	Roto Sil	795471 <input type="checkbox"/>	
	2201 – 2400	2290	200	640	J	J	4	Roto Sil	795473 <input type="checkbox"/>	



INFORMAZIONI

Dispositivo falsa manovra (arresto asta leva) premontato di serie.



INFORMAZIONI

Nell'utilizzo di aste leva standard (RC 1 N, RC 2, RC 2 N) utilizzare la guida articolazione per anta a ventola
 → *da pagina 240*