




#### 4.8.2.3.2 Entrata da 8 a 50 mm



									N°
8	431 – 620	400	100 / 100	194 - 289	N	N	–	Roto Sil	795525 <input type="checkbox"/>
15	621 – 800	680	100 / 100	290 - 379	J	N	1	Roto Sil	795526 <input type="checkbox"/>
25	801 – 1200	980	200 / 200	380 - 579	J	N	1	Roto Sil	795527 <input type="checkbox"/>
30									
35	1001 – 1400	1180	200 / 200	480 - 679	J	N	1	Roto Sil	795528 <input type="checkbox"/>
40	1201 – 1600	1380	200 / 200	580 - 779	J	N	2	Roto Sil	795529 <input type="checkbox"/>
45									
50	1601 – 2000	1780	200 / 200	780 - 979	J	J	2	Roto Sil	795530 <input type="checkbox"/>
	2001 – 2400	2180	200 / 200	980 - 1179	J	J	4	Roto Sil	795531 <input type="checkbox"/>




#### INFORMAZIONI

Dispositivo falsa manovra (arresto asta leva) premontato di serie.

#### 4.8.3 Cava euro 7/8

##### 4.8.3.1 Sede maniglia costante



									N°
15	431 – 630	520	200	195	J	N	–	Roto Sil	839919 <input type="checkbox"/>
25	601 – 800	690	200	335	J	N	1	Roto Sil	331943 <input type="checkbox"/>
30									
35	801 – 1000	890	200	490	J	N	2	Roto Sil	331964 <input type="checkbox"/>
40									
45									
50									